

**Gates** **BARRICADE**<sup>®</sup>  
FUEL INJECTION HOSE

- COVER:** Outstanding ozone and heat resistance
- REINFORCEMENT:** Textile spiral weave provides best-in-class working psi\*
- ADHESION LAYER:** Serves as a second defense against oil and aggressive fuels
- GREENSHIELD<sup>®</sup> BARRIER:** Patent-pending thermoplastic material delivers the lowest permeation in the industry
- BARRIER TUBE:** Fortified to resist high heat and aggressive fuels such as Ethanol

- High temperature, low permeation, multi-fuel compatible hose that eliminates fuel vapour loss
- Compatible with all fuels ( including E-85, Methanol and Ethanol based fuels )
- GREENSHIELD<sup>®</sup> BARRIER: Thermoplastic material delivers the lowest permeation in the industry.
- Best in Class working psi of 225 ( for fuel injection )
- Lowest permeation rate on the market 1gr/m<sup>2</sup>/day
- Hose ID Size: 7.94mm or 0.375" (5/16") - Hose OD Size: 14.73mm or 0.580".
- Compatible with Speedflow 401- 408 Pushlock Hose Ends & 411 to 421 Push On Hose Ends.
- Part Number: 485-05
- Compatible with Leaded, Unleaded, Diesel, Biodiesel, E-85, 100% Methanol, ETHANOL and Gasohol Fuel.